

**Series 2, wall-mounted cooker hood,
60 cm, Stainless steel
DWP64CC50M**



**The wall-mounted chimney hood: mount it
on the wall, giving you complete freedom in
your kitchen planning.**

- **Silent:** maximal extractor performance with little noise
- With exhaust, the air is cleaned by a grease filter and then ducted to the outside which ensures optimal kitchen air quality.
- 3-Speed Power Level Options To Suit Your Cooking Style And Recipes

Technical Data

Typology : Wall-mounted
 Length electrical supply cord : 120 cm
 Height of the chimney : 410-765/410-765 mm
 Height of product, without chimney : 250 mm
 Net weight : 9.2 kg
 Type of control : mechanical
 Number of speed settings : 3
 Maximum output air extraction : 380 m³/h
 Maximum output recirculating air : 235 m³/h
 Number of lights : 2
 Noise level : 64 dB(A) re 1 pW
 Diameter of air outlet : 150 mm
 Grease filter material : Washable aluminium
 Odour filter : No
 Operating Mode : Convertible
 Optional accessories : DWA0KP6A, DWZ6HP1U2
 Type of lamps used : LED
 Total power of the lamps : 10 W
 Grease filter type : Kasette
 Connection Rating : 135 W
 Voltage : 220-240 V
 Frequency : 50 Hz
 Plug type : GB plug
 Installation typology : Wall-mounted
 Material body : Stainless steel
 Plug type : GB plug
 Dimensions of the product, with chimney (if exists) (in) : / x x
 Dimensions of the packed product : 15.74 x 23.22 x 28.34
 Net weight : 20.000 lbs
 Gross weight : 32.000 lbs
 Motor location : Integrated motor in hood body
 No-return airflow flap : No
 Length electrical supply cord : 120 cm
 Dimensions of the product, with chimney (if exists) : 790-1015 x 598.0 x 470.0 mm
 Dimensions of the packed product (HxWxD) : 400 x 590 x 720 mm
 Net weight : 9.2 kg
 Gross weight : 14.3 kg



Series 2, wall-mounted cooker hood, 60 cm, Stainless steel DWP64CC50M

**The wall-mounted chimney hood: mount it
on the wall, giving you complete freedom in
your kitchen planning.**

Variant:

Design:

- Appliance colour: stainless steel
- Wall mounted hood

Comfort:

- Suitable for ducted or re-circulated extraction
- 3 speeds
- push buttons for extractor speeds and light
- Metal grease filter, dishwasher safe
- Charcoal filter

Environment and Safety:

- Energy Efficiency Class: D*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 72.8 kWh/year*

Technical Info:

- Maximum extraction rate exhaust air 380 m³/h according to EN 61591
- Extraction rate in recirculation mode:
Max. normal use: 235 m³/h
- Noise min./max. Normal Level: 53/64 dB*
- Noise level in recirculation mode:
Max. normal use: 70 dB(A) re 1 pW (56 dB(A) re 20 µPa sound pressure)
- Power rating: 135 W
- Light Intensity: 1000 lux
- Colour Temperature: 4000 K

Measures:

- Electrical cable length 1.2 m
- Diameter pipe Ø 150 mm (Ø 150 mm enclosed)
- Dimensions exhaust air (HxWxD): 790 - 1015 x 598 x 470 mm
- Dimensions recirculating (HxWxD): 790 - 1015 x 598 x 470 mm

**Series 2, wall-mounted cooker hood, 60 cm,
Stainless steel
DWP64CC50M**

